



Data Guide

POLYURETHANE VARNISH

PRODUCT DESCRIPTION

Norski Polyurethane Varnish has been specially formulated for ease of use, with maximum protection and manufactured in gloss or satin finish. Ideal for floors, plywood, timber and chipboard. Norski Polyurethane requires no special thinners or mixing, simply stir the Polyurethane well and apply with either a brush or roller.

Produces a hard wearing, smooth finish.

PREPARATION

Sand the surface which is to be varnished - it must be smooth and free of dust. Take care in removing all traces of wax. Interior wood may be stained using spirit or water stains. If the surface has been stained, allow to dry, sand lightly where the grain has been raised.

Do not seal with lacquer type sanding sealer. Cork needs no preparation, other than thoroughly cleaning and ensuring it is dust free.

First Coat: Stir well, then apply the polyurethane from the can, either by brush or roller. Allow 4-8 hours to dry.

Fill nail holes and cracks with Norski Epoxy Filler or Norski Staybond, allow the filled areas to dry, then lightly scuff all surfaces with sandpaper.

Following Coats: Repeat with 4-5 coats. Obviously the more coats applied, the better the resulting finish, your job will weather better with another layer.

DRYING TIME

Surfaces may be walked on after overnight drying, leave 24 hours before hard traffic.

THINNERS

Use Mineral Turpentine for thinning and cleaning brushes.

COVERAGE

Approximately 12 sq.meters per litre.

CLEANING

Clean work equipment with Mineral Turpentine.

SUPPLIED

In the following sizes: 500ml, 1 Ltr, 2 Ltrs, 4 Ltrs, 20 Ltrs.



SAFETY PRECAUTIONS: Do not use near fire or flames. Harmful or fatal if swallowed Use disposable gloves to avoid skin contamination. If resin comes into contact with skin, wash uncured resin off with soap and water. Wear safety glasses to avoid eye contamination. Mixed formulation contains Epoxy Resin and Amines. If swallowed do not induce vomiting. Give a glass of water. Contact a Doctor or the Poisons National Information Centre on 0800 764 766 (Urgent information only). Eye Contamination: Hold eyes open and flood with water for at least 15 minutes. See a Doctor immediately.

WARRANTY

Because the use of this product is beyond the control of the manufacturer, no liability or responsibility can be accepted for any loss or damage arising from its application or use. Liability for faulty material is limited to product replacement only.