



Data Guide

TIMBER SEALER

PRODUCT DESCRIPTION

A penetrating two component preservative containing fungicides which hardens and preserves timber.

AREAS OF USE

Preservation of timber in rebuilding work and where extra protection is required in new work. In bldges and behind fittings where access is limited. Suitable for use as a primer for masonry surfaces where mould has been a problem. Application of Epoxy Filler once Timber Sealer is applied can be done to reconstitute areas where timber has rotten away. Product can be used on flooring such as chipboard to enhance life of floor.

LIMITATIONS

Will not resurrect already rotten timber, however, thorough treatment of doubtful timber can be extremely effective.

MIXING

A 1: 1 ratio is used and the mixture should be thoroughly stirred to fully blend the two components.

For maximum penetration, use small mixes so that the material is used within its pot life.

Coverage = 10 Sq Meters/litre

APPLICATION

By brush or roller and flood the surface to be treated. All contamination should have been removed prior to treatment, and timber should be dry and not water logged. A primer coat can be given to improve penetration. **Mix Timber Sealer with Epoxy Thinners 20%**. On un-coated timbers an extra coat may be necessary to ensure adequate sealing and penetration. To obtain very deep penetration, apply wet resin on wet resin. Repeat until surface refuses to absorb any more. Once the resin has set, there will be no further penetration into the wood. Successive coats will produce a very hard glossy surface. A general rule of thumb with this product is the more coats the better.

CURING

A slow release in viscosity indicates the end of the pot life. Best penetration is obtained from freshly mixed material. Allow to cure overnight between coats. Where wet on wet treatment is used, a final coat 24 hours later is recommended.

SAFETY PRECAUTIONS: Do not use near fire or flames. Harmful or fatal if swallowed Use disposable gloves to avoid skin contamination. If resin comes into contact with skin, wash uncured resin off with soap and water. Wear safety glasses to avoid eye contamination. Mixed formulation contains Epoxy

Norski Holdings Ltd, 10 Northpoint St, Plimmerton Wellington 5024
Phone 04 233 6184, Facsimile 04 233 6173, Website www.norski.co.nz



Resin and Amines. If swallowed do not induce vomiting. Give a glass of water. Contact a Doctor or the Poisons National Information Centre on 0800 764 766 (Urgent information only). Eye Contamination: Hold eyes open and flood with water for at least 15 minutes. See a Doctor immediately.

WARRANTY

Because the use of this product is beyond the control of the manufacturer, no liability or responsibility can be accepted for any loss or damage arising from its application or use. Liability for faulty material is limited to product replacement only.