

SAFETY DATA SHEET

Issue Date February 2018

Section 1: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product identifier
Product Name EPOXY MORTAR BASE
Description RESIN PASTE

Other means of identification

UN Number 3082 Environmentally Hazardous Liquid NOS.

Recommended use of the chemical and restrictions on use
RECOMMENDED USE CONSTRUCTION OF EQUIPMENT AND FITTINGS

Details of the supplier of the safety data sheet

Manufacturer
Norski Holdings Ltd
10 Northpoint Street
Plimmerton
Wellington 5247
New Zealand

For further information, please contact

Contact Point

Norski Holdings Ltd
+64 (04) 233 6184

E-mail address

Enquiries@norski.co.nz

Emergency telephone number

Emergency Telephone

0800 500 341

Section 2: HAZARD(S) IDENTIFICATION

Regulatory information

EPA New Zealand HSNO Approval Code or Group Standard

HSR002670 the Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017

DANGEROUS GOODS CLASS 9 PACKING GROUP III

GHS and HSNO CLASSIFICATIONS

Acutely Toxic (Oral, Dermal and Inhalation)	Category 4 (HSNO-6.1D)
Skin Corrosion/Irritation	Category 2 (HSNO - 6.3A)
Serious Eye Damage/Eye Irritation	Category 2A (HSNO – 6.4A)
Skin Sensitisation	Category 1 (HSNO -6.5B)
Specific Target Organ Repeated Exposure (Lungs)	Category 1 (HSNO 6.9A)
Chronic Aquatic Toxicity	Category 2 (HSNO - 9.1B)

Signal Word

DANGER



Hazard statements

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H372 May cause damage to organs through long and repeated exposure
- H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements – Prevention

- P261 Do not breathe mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – Response

- P301 + P312 IF SWALLOWED:** Call a POISON CENTER or doctor/physician if you feel unwell.
- P330** Rinse mouth.
- P302 + P352 IF ON SKIN:** Wash with plenty of soap and water.
- P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.
- P304 + P340 IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing.
- P305 + P351 + P338**
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313** If eye irritation persists: Get medical advice/attention.
- P312** Call a POISON CENTER or doctor/physician if you feel unwell.
- P321** Specific treatment (see First Aid Measures below)
- P363** Wash contaminated clothing before reuse.
- P391** Collect spillage

Precautionary Statements – Storage

P405 Store Locked Up.

Precautionary Statements – Disposal

P501 In NZ Dispose of in Accordance with EPA and Local Authority/Regional Council Requirements.

Section 3: COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Name	CAS no.	Weight %
Bisphenol A/ epichlorohydrin resin	25085-99-8	35-45
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	9003-36-5	2-6%
4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer	5068-38-6	35-45%

Section 4: FIRST AID MEASURES

Inhalation	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.
Skin Contact	Remove contaminated clothing/shoes and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Contaminated leather articles, including shoes,

cannot be decontaminated and should be destroyed to prevent reuse.

Eye contact	Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.
Ingestion Treatment	Do not induce vomiting. Rinse mouth with water. Give plenty of water to drink. Treat symptomatically

Section 5: FIREFIGHTING MEASURES

Extinguishing Media	Use water fog, foam, dry chemical or carbon dioxide.
Extinguishing Media to Avoid	Do not use direct water stream. May spread fire
Hazardous Combustion Products	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Phenolics. Carbon monoxide. Carbon dioxide.
Unusual Fire and Explosion Hazards	Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is emitted when burned without sufficient oxygen.
Fire Fighting Procedures	Clear fire area of all non-emergency personnel. Isolate fire and deny unnecessary entry. Cool fire exposed containers with water. Irritating fumes are released in fire situations. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Do not allow material or run-off to enter waterways. Stay upwind, keep out of low areas.
Fire-fighting equipment	Wear positive-pressure self-contained breathing apparatus (SCBA) and protective firefighting clothing (includes firefighting helmet, coat, trousers, boots, and gloves).

Avoid contact with this material during firefighting operations. If contact is likely, change to full chemical resistant firefighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location

HAZCHEM 3Z

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).



Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities

Large Spills

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small Spills

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7: HANDLING AND STORAGE

Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area,

away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Workplace Exposure Standards None established

Engineering Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants as low as possible and/or below any recommended or statutory limits. Use explosion-proof ventilation equipment.

Personal Respiratory - Use a properly fitted, air-purifying or air-fed respirator complying with New Zealand or EU standards if a risk assessment indicates this is necessary.

HANDS

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommended: polyvinyl alcohol (PVA), Butyl rubber, EVAL, Neoprene.

EYES

Safety eyewear complying with a New Zealand or EU Standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

This product is a grey paste once liquid constituents are combined.

Flash point	:	Greater than 150 °C (302 °F)
Evaporation rate	:	Not determined
Flammability	:	Non-flammable.
Explosion limits		
Upper:	:	Not determined
Lower:	:	Not determined
Vapor pressure	:	Less than 0,01 Pa @20 °C (68 °F)
Vapor density	:	Not determined
Relative density	:	Not determined
Solubility	:	Estimated. 0,009 kg/m ³ @23 °C (73 °F)

Partition coefficient: n-octanol/water	:	LogPow 3
Auto-ignition temperature	:	Greater than 300 °C (572 °F)
Decomposition temperature	:	Not determined
Viscosity	:	Kinematic-Not determined Dynamic- 12 - 14 Pa·s @25 °C (77 °F)

Section 10: STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Conditions to avoid	Avoid temperatures above 300°C. Potentially violent decomposition can occur, causing gas generation and pressure increases in closed systems.
Materials to avoid	Reactive or incompatible with the following materials: <i>oxidizing materials</i> Slightly reactive or incompatible with the following materials: <i>acids, amines, anhydrides, chloroform, chloroform acid.</i>
Hazardous Decomposition	Decomposition products may include the following materials: carbon oxides, phenolics and water.

Section 11: TOXICOLOGICAL INFORMATION

Potential Health effects

CAUSES DAMAGE TO BODY ORGANS THROUGH PROLONGED OR REPEATED CONTACT.

Inhalation	Vapours are unlikely due to physical properties.
Ingestion	Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.
Skin	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Eye	May cause eye irritation. Corneal injury is unlikely.

**Acute Health Effects
(Bisphenol A/ epichlorohydrin resin)**

Test	Species	Result	Exposure
LD50 Oral	Rat	>5000mg/kg	-
LD50	Rabbit	20,000mg/kg	-

Dermal

Acute toxicity

Hazardous ingredient name

4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer

LD50 Oral	Rat	30.000 mg/kg
LD50 Dermal	Rat	> 1.200 mg/kg

Systemic Effects

Carcinogenicity

Mutagenicity

Except for Skin sensitization, repeated exposure is not likely to cause significant adverse effects.

IARC has classified DGEBCA as non-carcinogenic.

In animal studies, did not cause birth defects or other adverse effects on the fetus when pregnant rabbits, did not interfere with reproduction. Animal genetic toxicity studies were negative.

Section 12: ECOLOGICAL INFORMATION

Bisphenol A/ epichlorohydrin resin)

Ecotoxicity Material is moderately toxic to aquatic organisms on an acute basis

	Species	Period	Result
LC50	fathead minnow	96 h	3.1 mg/l
EC50	water flea	48 h	1.4 - 1.7 mg/l
IC50	bacteria	18 h	> 42.6 mg/l

Degradability

Bioaccumulation

HSNO

Classification

Under OECD guidelines this material cannot be considered as readily degradable.

Moderate

Log Pow = 3 - 5

9.1B Very ecotoxic in the aquatic environment

This material including 4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer is toxic to aquatic life with long lasting effects.

Section 13: DISPOSAL CONSIDERATIONS

Dispose of Product in Accordance with Local Authority and Regional Requirements. EPA and WorkSafe New Zealand requirements must also be met.

Section 14: TRANSPORT INFORMATION

Regulatory information	UN/NA number	Proper shipping name	Classes/*PG	Additional information
NZS 5433 Land Transport	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.contains (LIQUID EPOXY RESIN)	Class 9 III	
IMO/IMDG	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. contains (LIQUID EPOXY RESIN, LIQUID EPOXY RESIN)	Class 9 III	
IATA (Cargo)	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. contains (LIQUID EPOXY RESIN)	Class 9 III	



Section 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

New Zealand

The Person in Control of a Business Unit must ensure that the requirements of Regulations 15-20 of the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016 relating to Personal Protective Equipment are met with regards to all those who work with the Epoxy Mortar Base.

The Person in Control of a Business Unit must also comply with the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016 as they cover Risk Management, First Aid Equipment including Eye Wash, Training, Emergency Management, Health and Exposure Monitoring and provision of Information for Epoxy Mortar Base.

After June 2018 the Person in Control of a Business Unit must ensure that the Training Provisions of Regulation 4.5 of the Health and Safety at Work (Hazardous Substances) Regulations 2017 are met in relation to Epoxy Mortar Base.

The Group Standard applying Disposal, Labelling, Packaging and Safety Data Sheet requirements to this product and HSNO Approval Number is the Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017 HSR 002670. Prior to 1 December 2017 all Site and Storage Controls relevant to Epoxy Mortar Base were contained in this Group Standard.

Section 16: ANY OTHER RELEVANT INFORMATION

Revision Date February 2018

Revision Note New Format

Key or legend to abbreviations and acronyms used in the data safety sheet

Disclaimer

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.

End of Safety Data Sheet